

TV Card Features

Table of Contents

- [1 Overview](#)
- [2 Introduction](#)
- [3 Supported Tuners](#)
- [4 Unsupported Tuners](#)
- [5 Special Features](#)
 - [5.1 DVB-C Tuners](#)
 - [5.2 DVB-S/S2 Tuners](#)
 - [5.3 DVB-T/T2 Tuners](#)
 - [5.4 Video Capture Cards](#)
- [6 Feature Explanation](#)
 - [6.1 CI/CAM](#)
 - [6.2 CI Menu](#)
 - [6.3 Multi-channel Decryption](#)
 - [6.3.1 Digital Devices Tuners](#)
 - [6.3.2 Multichannel decryption example](#)
 - [6.3.3 Multidecrypt example](#)
 - [6.4 DiSEqC](#)
 - [6.5 DVB-S2](#)
- [7 Related](#)

Overview

A general reference to tuner features supported by MediaPortal.

Introduction

This page is not intended to be a complete list of all tuners supported by MediaPortal. MediaPortal supports far too many tuners to be able to list all of them individually. If you want to know whether a particular tuner is supported:

1. Check the "rules" for supported tuners below.
2. Check the unsupported tuner/feature list.
3. Check the forums for reports of compatibility problems.

Supported Tuners

If your tuner has a BDA driver (most DVB and ATSC/QAM tuners do) and is not listed in the unsupported list then there is a very good chance that it will work.

In general, MediaPortal's TV Server supports:

1. **Any DVB/ATSC** card which has **BDA** drivers. This includes the vast majority of all tuner cards available today.
2. **All** analog tuners with dedicated hardware for video and audio encoding on board, and DirectShow-compatible **WDM** drivers.
3. **Some** analog tuners which require software to encode the video and audio. The tuner card must not require a connection to the "Line In" or "Microphone" input of a sound card to make the audio work. Not all **software encoders** are compatible with TV Server.
4. The TechniSat SkyStar-2/Airstar-2/CableStar-2 tuners, when using the **WDM** driver. The **BDA** driver is not stable.
5. The **Hauppauge Colossus** and **HD PVR** video capture devices. TV Server also supports capture inputs on cards with analog tuners, however **other capture cards without tuners are currently not supported**.
6. **CableCARD** tuners: Ceton, Hauppauge and Silicondund tuners are supported. ATI TV Wonder support is unknown. Hauppauge tuners require **driver 2.4_20140121_32028** or later. Silicondund tuners require 20130708beta1 firmware or later.

Unsupported Tuners

The following tuners are currently unsupported or not yet fully supported:

- Anysee (DiSEqC, CI)
- AVerMedia (DiSEqC, CI) - please petition them if you want support for these features in MediaPortal
- Blackgold (DiSEqC)
- Compro (DiSEqC)
- DVBSky (CI)
- KWorld DVB-S100 - this tuner uses a proprietary method to control the power supply to the LNB; KWorld have not responded to our requests for an SDK/documentation
- KNC TV-Station DVB-S2 Twin (DVB-S2, DiSEqC, CI) - DVB-S tuning should work if you use the DVB-S network provider
- Omicom (DiSEqC)
- Pinnacle/PCTV Systems (DiSEqC)

- Realtek RTL2832U and RTL2832P based tuners (DAB, FM) - these Realtek chipsets are used in many tuners (eg. DigitalNow Dabby and Quad, Mygica T803 and T188) that support DVB-T/T2 and/or DVB-C with DAB/DAB+ and FM radio. DVB-T/T2 functions work fine, however DAB and FM functions are not supported at this time. DVB-C support may depend on the driver used.
- TBS (CI) - supported with a [patch](#) [tbs-ci-cam-support-and-other-improvements.103276] from our forum
- TechnoTrend Budget CT2-4500 CI, Connect CT2-4650 CI (CI)
- TechnoTrend Premium
- TeVii H700, S700 (CI)
- TerraTec H7, S7 revision 4 (CI)

Special Features

The following tables list the **special features** of various tuners that are supported by MediaPortal. It is **not** meant to be a list of each supported tuner.

DVB-C Tuners

Model /Brand	CI/CAM support	CI menu support	Multi-channel decryption	Remarks
Digital Devices	Yes	Yes	No	Cine CT, Cine CT2, Cine C2T2, DuoFlex CT, DuoFlex CT2, DuoFlex C2T2 DVB-C2 is currently not supported.
Digital Everywhere	Yes	Yes	Yes	FloppyDTV-C Digital Everywhere is no longer in business but Digital Devices are still selling the Digital Everywhere FloppyDTV DVB-C.
Hauppauge	Yes	Yes	No	The WinTV CI can be used with Nova and HVR series tuners.
KNC	Yes	Yes	No	TV-Station DVB-C
Mystique	Yes	Yes	No	CaBiX-C2
TechniSat	Yes	No	No	CableStar Combo HD CI, CableStar HD2
TechnoTrend	Yes	Yes	Yes	Budget C-1501, Connect CT-3650 CI
TerraTec	Yes	No	No	Cinergy 1200 DVB-C, Cinergy C PCI HD, H7 (rev. 1, 2, 3)
Twinhan (Azurewave)	Yes	No	No	AD-CP400

DVB-S/S2 Tuners

Model /Brand	CI /CAM support	CI menu support	Multi-channel decryption	DiSEqC - switch	DiSEqC - motor	Remarks
Digital Devices	Yes	Yes	No	Yes	No	Cine S2, DuoFlex S2
Digital Everywhere	Yes	Yes	Yes	Yes	Yes	FloppyDTV-S, FloppyDTV-S2
DVBSky	No	No	No	Yes	Yes	S830, S850, S860, S950, S950C, S952, S960, S960C
Genpixmap	No	No	No	Yes	No	SkyWalker 1, SkyWalker 2 Open source driver.
Hauppauge	Yes	Yes	No	Yes	Yes	HVR-3000, HVR-3300, HVR-4000, HVR-4400, NOVA HD-S2, NOVA HD-USB2, NOVA S Plus, NOVA S-USB2 The WinTV CI can be used with Nova and HVR series tuners.
KNC	Yes	Yes	No	Yes	No	TV-Star DVB-S, TV-Station DVB-S, TV-Station DVB-S2
Mystique	Yes	Yes	No	Yes	No	SaTiX SE, SaTiX SX, SaTiX S2, SaTiX S2 Dual
Prof	No	No	No	Yes	Yes	Red 6200 PCI, Red 7300 PCI, Revolution 7301 PCI, Revolution 7500 USB, Revolution 8000 PCIe, AdvanceTune 7700 USB, AdvanceTune 8700 PCIe
TBS	No	No	No	Yes	Yes	QBOX, QBOX S2, QBOX 3, TBS5922, TBS5922SE, TBS5925, TBS5980, TBS5990, TBS6920, TBS6921, TBS6922, TBS6922 SE, TBS6925, TBS6928, TBS6928SE, TBS6980, TBS6981, TBS6982, TBS6983, TBS6984, TBS6985, TBS6991, TBS6991SE, TBS6992, TBS8920, TBS8921, TBS8922
TechniSat	Yes	No	No	Yes	Yes	SkyStar 2, SkyStar HD2, SkyStar S2, SkyStar USB HD, SkyStar USB 2 HD CI
TechnoTrend	Yes	Yes	Yes	Yes	Yes	Budget S-1500, Budget S2-1600, Budget S2-3200, Budget S2-4100, Connect S-2400 Connect S2-3600, Connect S2-3650 CI, Connect S2-4600
TerraTec	Yes	No	No	Yes	Yes	Cinergy S PCI, Cinergy S USB, Cinergy S2 PCI HD, Cinergy S2 PCIe DUAL, Cinergy S2 USB HD, Cinergy S2 USB BOX, S7 (rev. 1, 2, 3)
TeVii	No	No	No	Yes	Yes	S420, S421, S464, S470, S471, S480, S482, S630, S632, S660, S662
Twinhan (Azurewave)	Yes	No	No	Yes	Yes	AD-SP400, Sat-Ci

DVB-T/T2 Tuners

Model/Brand	CI/CAM support	CI menu support	Multi-channel decryption	Remarks
Digital Devices	Yes	Yes	No	Cine CT, Cine CT2, Cine C2T2, DuoFlex CT, DuoFlex CT2, DuoFlex C2T2
Digital Everywhere	Yes	Yes	Yes	FloppyDTV-T
Hauppauge	Yes	Yes	No	The WinTV CI can be used with Nova and HVR series tuners.

KNC	Yes	Yes	No	TV-Station DVB-T
Mystique	Yes	Yes	No	TeRiX-T2
TechnoTrend	Yes	Yes	Yes	Connect CT-3650 CI
TerraTec	Yes	No	No	H7 (rev. 1, 2, 3)
Twinhan (Azurewave)	Yes	No	No	AD-TP300

Video Capture Cards

Model / Brand	Configurable bit-rate	Remarks
Hauppauge Colossus	Yes	Colossus is a <i>High Definition</i> video recorder for making real-time H.264 compressed recordings at resolutions up to 1080i. HD PVR records component video (YCrCb) from video game consoles and cable TV and satellite set top boxes. * Includes a built-in high quality hardware H.264 high definition encoder, for high performance, high quality video recordings * Record high definition video at up to 1080i resolution. Also records standard definition video. Record at datarates from 1Mbs to 20Mbs.
Hauppauge HD PVR	Yes	HD PVR is the world's first <i>High Definition</i> video recorder for making real-time H.264 compressed recordings at resolutions up to 1080i. HD-PVR records component video (YCrCb) from video game consoles and cable TV and satellite set top boxes.

Feature Explanation

CI/CAM

Some cards have a [CI/CAM](#) slot. Some examples are shown below:



The CI slot allows you to watch encrypted (pay TV) channels when you insert an appropriate CAM and smart card. It is not possible to watch encrypted channels without a CI slot, CAM and smartcard.


CI Menu

CAMs generally have a service menu that allows you set parental control settings and view information about your subscription, smart card and CAM. If your card supports it, MediaPortal allows you to access the service menu in two ways:

1. from the fullscreen TV context menu (**? Unknown Attachment** or Info/More key)

? Unknown Attachment

1. from TV-Server Configuration



Multi-channel Decryption

Multi-channel decryption is the ability to decrypt **multiple channels** from a **single transmitter** (also referred to as a transponder, frequency, mux or multiplex) with a **single tuner**. Both the tuner and CAM must support decrypting multiple channels for this feature to work.

Digital Devices Tuners

Digital Devices tuners support an additional feature called multidecrypt (MTD) which many people confuse with multi-channel decryption.

Multidecrypt is the ability for **multiple tuners** to share a **single CAM**.

Digital Devices tuners support both multi-channel decryption and multidecrypt (CAM sharing). However, multi-channel decryption only works when multidecrypt is disabled. In other words, when a CAM is shared by multiple tuners (ie. multidecrypt is active) each tuner can only use the CAM to decrypt one channel.

MediaPortal only supports multidecrypt with Digital Devices tuners. Multi-channel decryption is not supported. Multidecrypt with multiple CAMs (chaining) is supported with a [patch](#).

Multichannel decryption example

A single Digital Everywhere FloppyDTV S2 card can decrypt multiple channels from a single transponder with a single CAM.

Multidecrypt example

A Digital Devices Cine S2 card with its two DVB-S2 tuners can use one CAM to decrypt two channels from any two transponders. Both tuners must be used to decrypt the two channels, even if the channels are broadcast on the same transponder.

DiSEqC

[DiSEqC](#) is a communication protocol that allows satellite tuners, switches, [LNBS](#), dish motors (positioners), and other related satellite equipment to work together. It is most commonly used by satellite tuners to control a switch or motor that enables you to receive channels from multiple satellites.

The picture below shows a dish with four LNBS. Each LNB is connected to an input on a DiSEqC switch, which is in turn connected to one or more tuners. When the owner of this dish wants to watch a channel, their tuner must use DiSEqC commands to select the correct LNB corresponding with the satellite which broadcasts the channel that the person wants to watch.



DVB-S2

DVB-S2 is the second generation DVB satellite broadcasting standard. It is commonly used to transmit [HDTV H.264](#) channels since the better compression and modulation techniques allow HD channels to be transmitted using the same bandwidth as a normal [SDTV MPEG-2](#) channel.

Related

References

- [CAMs \(Conditional Access Modules\)](#)

2011-10-17T05:34:28Z